



STRETCH WRAPPING MACHINES

Power pre Stretch – Palette Wrapping Machine – MH-FG- 2000 B

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS		Film Data	
Model No	MH – FG – 2000 B	Type	LLDPE / LDPE stretch film
Power	220 V / 1 P / 50 Hz/ 1 KW	Internal core dia	50 mm - 76 mm
Turn Plate speed	0 - 12 rpm	External core dia	</= 250 mm
Turn Plate Dia	1500 mm	Height	100 mm – 500 mm
Pillar Height	2400 mm	Thickness	17 – 25 Microns
Max. Ht. of the palette	2000 mm	Stretchability	up to 300%

Power pre Stretch – Box Wrapping Machine – MH-FG-800 B

TECHNICAL SPECIFICATIONS

Power Supply	1P /AC220V/50Hz /0.75KW	Film Data:	
Air pressure	5kg/cm ² ~7kg/cm ²	Parameter of film	PE Stretch film
Air consumption	0.7m ³ /hr	Width	12" or 16"
Machine size	W470mm×L1510mm×H2110mm	Thickness	17~25µm
Speed of turntable	20r/min (adjustable)	Outside diameter	≤250mm, diameter of inside
Product weight	Within 80kg	Paper core	50~76mm
Wrapping height	Height:300~820mm	Stretch rate	100%~300%
Product specification	Diagonal up to 1000mm		
Mode of outputting film	Pre-stretch with mechanical and power system		